



DS1982U/DS1985U

UniqueWare™ iButton®

SPECIAL FEATURES

- 1024 bits or 16Kb Electrically Programmable Read Only Memory (EPROM) communicates with the economy of one signal plus ground
- Unique, factory lasered and tested 64-bit registration number (8-bit family code, 3-bit serialization, 12-bit UniqueWare Identifier 5E7h, 8-bit CRC tester) assures absolute traceability because no two parts are alike
- EPROM partitioned into 256-bit pages for randomly accessing packetized data records
- Each memory page can be permanently write-protected to prevent tampering
- Device is an “add only” memory where additional data can be programmed into EPROM without disturbing existing data
- Reduces control, address, data, power and programming signals to a single pin
- 8-bit family code specifies device communications requirements to reader
- Presence detector acknowledges when reader first applies voltage
- Reads over a wide voltage range of 2.8V to 6.0V from -40°C to +85°C

COMMON iButton FEATURES

- Multidrop controller for 1-Wire network
- Digital identification and information by momentary contact
- Chip-based data carrier compactly stores information
- Data can be accessed while affixed to object
- Economically communicates to bus master with a single digital signal at 16.3kbps
- Standard 16mm diameter and 1-Wire® protocol ensure compatibility with iButton® family
- Button shape is self-aligning with cup-shaped probes
- Durable stainless steel case engraved with registration number withstands harsh environments
- Easily affixed with self-stick adhesive backing, latched by its flange, or locked with a ring pressed onto its rim
- Presence detector acknowledges when reader first applies voltage
- Meets UL#913 (4th edit.); Intrinsically Safe Apparatus, Approved under Entity Concept for use in Class I, Division 1, Group A, B, C and D Locations (application pending)

DESCRIPTION

UniqueWare iButtons are factory-programmed versions of the DS1982 (1024 bit) and the DS1985 (16Kb Add-Only iButtons, respectively. They differ from the regular devices in their custom ROM family codes (see the Ordering Information) and the UniqueWare Identifier 5E7h in place of the upper 12 bits of the standard serialization field. For technical details on the devices, refer to the DS1982 and DS1985 data sheets.

UniqueWare Add-Only iButtons are only available preprogrammed with customer-specific and write-protected data. UniqueWare data fills at least one but no more than the first two pages of a device, depending on the length of the customer-supplied data.

UniqueWare devices are only available to existing customers. New data patterns are no longer accepted. The minimum order quantity (MOQ) is 34,000 pieces with higher quantities available in multiples of 17,000 pieces. UniqueWare iButtons can only be purchased in bulk form, delivered in bags. The shipment quantity can be plus or minus 10% of the order quantity. Only the quantity shipped will be billed.

*UniqueWare is a trademark of Maxim Integrated Products, Inc.
iButton and 1-Wire are registered trademarks of Maxim Integrated Products, Inc.*

Sample UniqueWare Data Structures

SAMPLE 1: ETHERNET NODE ADDRESS Figure 1a

(unused)	CRC16		Company ID Value		Extension ID Value		Project ID		Length
	MSB	LSB	MSB	LSB	MSB	LSB	MSB	LSB	
19 bytes FFh	2 bytes		3 bytes constant assigned by IEEE		3 bytes serialization		4 bytes constant		1 byte 0Ah

high address

low address

PHYSICAL ADDRESS AND DATA MAPPING Figure 1b

Address	0C	0B	0A	09	08	07	06	05	04	03	02	01	00
Data	xx	xx	ch	cm	cl	hh	mm	ll	00	00	pp	pp	0A

xx xx = inverted CRC16, value depends on actual data

ch cm cl = high, medium and low byte of the IEEE assigned "Company ID"

hh mm ll = high, medium and low byte of the "Extension ID" or serialization

pp pp = Project ID assigned by Maxim

SAMPLE 2: EUI-64 FireWire® NODE ADDRESS Figure 2a

(unused)	CRC16		Company ID Value		Extension ID Value		Project ID		Length
	MSB	LSB	MSB	LSB	MSB	LSB	MSB	LSB	
17 bytes FFh	2 bytes		3 bytes constant assigned by IEEE		5 bytes serialization		4 bytes constant		1 byte 0Ch

high address

low address

PHYSICAL ADDRESS AND DATA MAPPING Figure 2b

Address	0E	0D	0C	0B	0A	09	08	07	06	05	04	03	02	01	00
Data	xx	xx	ch	cm	cl	hh	hm	mm	ml	ll	00	00	pp	pp	0C

xx xx = inverted CRC16, value depends on actual data

ch cm cl = high, medium and low byte of the IEEE assigned "Company ID"

hh hm mm ml ll = high, medium and low byte of the "Extension ID" or serialization

pp pp = Project ID assigned by Maxim

The examples shown here use the Default Data Structure. This format is also known as UDP (universal data packet) and is commonly used in 1-Wire APIs. Therefore, if using one of those APIs one can call a high level function to read and verify the inverted CRC16. The UDP is defined in Application Note 114: [1-Wire File Structure](#), and the APIs can be found in the [1-Wire Software Development Kits](#).

ORDERING INFORMATION

MEMORY SIZE	FAMILY CODE	PACKAGE	ORDERING PART NUMBER
1024 bits (4 pages)	89h	F3 MicroCan F5 MicroCan	DS1982U-F3-pppp+ DS1982U-F5-pppp+
16Kb (64 pages)	8Bh	F3 MicroCan F5 MicroCan	DS1985U-F3-pppp+ DS1985U-F5-pppp+

pppp stands for the Project ID assigned to each individual data pattern at the time of the first order.

+Denotes a lead(Pb)-free/RoHS-compliant package.

REVISION HISTORY

REVISION DATE	DESCRIPTION	PAGES CHANGED
12/09	Changed the <i>Ordering Information</i> to lead(Pb)-free.	3
	Removed the DS1986U.	1, 2, 3
	Removed instructions on how to set up a UniqueWare project (no new projects).	1
	Added MOQ and shipment quantity information.	1
	Emphasized that the 16-bit CRC is inverted.	1
	Included an explanation of "Default Data Structure."	2
	Changed notation of hexadecimal numbers from H to h.	1, 2, 3