

SCOPE: FIXED OUTPUT, 10W CMOS, STEP-UP SWITCHING REGULATOR

<u>Device Type</u>	<u>Generic Number</u>
01	MAX641AM(x)/883B

Case Outline(s). The case outlines shall be designated in Mil-Std-1835 and as follows:

<u>Outline Letter</u>	<u>Mil-Std-1835</u>	<u>Case Outline</u>	<u>Package Code</u>
MAXIM SMD			
JA P	GDIP1-T8 or CDIP2-T8	8 LEAD CERDIP	J8

Absolute Maximum Ratings

Supply Voltage, V_{OUT}	+18V
Output Voltage, L_X and LBO	+18V
Input Voltage, LBI, LBO, VFB and COMP	-0.3V to ($+V_{OUT}+0.3V$)
L_X Output Current	450 mA Peak
LBO Output Current	50mA

Lead Temperature (soldering, 10 seconds)	+300°C
Storage Temperature	-65°C to +150°C

Continuous Power Dissipation	$T_A=+70^\circ\text{C}$
8 lead CERDIP(derate 8.0mW/°C above +70°C)	640mW
Junction Temperature T_J	+150°C
Thermal Resistance, Junction to Case	
8 lead CERDIP, θ_{JC} :	55°C/W
Thermal Resistance, Junction to Ambient	
8 lead CERDIP. θ_{JA} :	125°C/W

Recommended Operating Conditions.

Ambient Operating Range (T_A)	-55°C to +125°C
Supply Voltage Range (V_S)	2.4V dc to 16.5V dc
Output Voltage Range (V_{OUT})	2.4V dc to 16.5V dc

Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TABLE 1 ELECTRICAL TESTS

PARAMETER	Symbol	CONDITIONS -55 °C ≤ T _A ≤ +125 °C V _{IN} = +3.0V Unless otherwise specified	Group A Subgroup	Device type	Limits Min 1/	Limits Max 1/	Units
Operating Voltage	+V _S	Voltage at V _{OUT}	1,2,3	All	2.0	16.4	V
Start-up Voltage	V _{SU}	Voltage at V _{OUT}	1 2,3	All	1.5 1.8		V
Supply Current NOTE 1	I _S	L _X Off, V _{OUT} = +5V	1,2,3	All		0.4	mA
Reference Voltage	V _{REF}		1 2,3	All	1.24 1.20	1.38 1.42	V
Output Voltage	V _{OUT}	No load, V _{FB} = GND, NOTE 1	1,2,3	All	4.75	5.25	V
Oscillator Frequency Range	f _O	V _{OUT} = +5V	4	All	40	50	kHz
Oscillator Duty Cycle	O _{DC}		4	All	40	60	%
LX On Resistance	R _{LXON}	I _X = 100mA, V _{OUT} = 5V V _{OUT} = 15V	1	All		12 7	Ω
Leakage Current	I _{LX}	V _{LX} = 16.5V	1 2,3	All		1 100	μA
Diode Forward Voltage	V _F	I _F = 100mA	1	All		1.0	V
VFB Input Bias Current	I _{FB}		1	All		10	nA
Low Battery Input Bias Current	I _{LBI}		1	All		10	nA
Low-Battery Output Current	I _{LBO}	V _{LBO} = 0.4V, V _{LBI} = 1.1V	1,2,3	All	0.5		mA
Low Battery Output Leakage Current	I _{LBOL}	V _{LBO} = +16.5V, V _{LBI} = +1.4V	1,2,3	All		3.0	μA

NOTE 1: Guaranteed by correlation with DC pulse measurements.

ORDERING INFORMATION	MAXIM PART NUMBER	SMD NUMBER
01	MAX641AMJA/883B	5962-9325401MPA

TERMINAL NUMBER	8 LEAD CERDIP
1	LBI
2	LBO
3	GND
4	LX
5	VOUT
6	EXT
7	V _{FB}
8	COMP

QUALITY ASSURANCE

Sampling and inspection procedures shall be in accordance with MIL-Prf-38535, Appendix A as specified in Mil-Std-883.

Screening shall be in accordance with Method 5004 of Mil-Std-883. Burn-in test Method 1015:

1. Test Condition, A, B, C, or D.
2. TA = +125°C minimum.
3. Interim and final electrical test requirements shall be specified in Table 2.

Quality conformance inspection shall be in accordance with Method 5005 of Mil-Std-883, including Groups A, B, C, and D inspection.

Group A inspection:

1. Tests as specified in Table 2.
2. Selected subgroups in Table 1, Method 5005 of Mil-Std-883 shall be omitted.

Group C and D inspections:

- a. End-point electrical parameters shall be specified in Table 1.
- b. Steady-state life test, Method 1005 of Mil-Std-883:
 1. Test condition A, B, C, D.
 2. TA = +125°C, minimum.
 3. Test duration, 1000 hours, except as permitted by Method 1005 of Mil-Std-883.

TABLE 2. ELECTRICAL TEST REQUIREMENTS

Mil-Std-883 Test Requirements	Subgroups per Method 5005, Table 1
Interim Electric Parameters Method 5004	1
Final Electrical Parameters Method 5005	1*, 2, 3, 4
Group A Test Requirements Method 5005	1, 2, 3, 4
Group C and D End-Point Electrical Parameters Method 5005	1

* PDA applies to Subgroup 1 only.